

World standard of multi cutting plotter

CG-FX series **CG-75FX** CUTTING PLOTTER / **CG-130FX** CUTTING PLOTTER / **CG-160FX** CUTTING PLOTTER

- High speed continuous crop mark detection
- Automatic media cut (Y direction)

FX Series



NEW! **CG-160FX**
CUTTING PLOTTER

Expressiveness and Functionality

Create Stickers Without Pattern!



Nesting with the Inkjet plotter JV3 series



Cutting with the CG-FX series as a Print-cut solution




Equipped with Plug-in cutting software
"Fine Cut 3" for CorelDRAW and
"Fine Cut 5" for Illustrator

- Selectable clamp pressure with high and low setting to permit a more accurate cut.
- Selectable jog speed of low/medium/high settings to ensure proper and easy positioning of the media.
- You can load media from back or front.
- RS232C, USB interface is available.
- The media roll holder will hold a total of 6 rolls simultaneously.
- Optional and exclusive pen adapter can be used.
- Pouncing tool is available as an option.



The Optical sensor comes with a LED pointer (Light pointer) for ease of use.



High speed continuous crop mark detection

An optical sensor enables automatic consecutive detection of registration marks throughout the nested image which the Inkjet printers print, in combination with the automatic correcting feature that allows you to obtain a precise contour cut.

A much more accurate cut by constantly detecting a maximum of 4 points continuously and even allowing the user to input number of copies in each X/Y direction.

Engineered Head Unit

Automatic sheet cutter mechanism provides great flexibility and enhance performance.



Automatic sheet cutter Light pointer Swivel cutter



Functional and advanced design

- Easy operation with back-lit front panel.
- Convenient compartment located on the upper portion of the frame.



Specifications

Item	CG-75FX	CG-130FX	CG-160FX
Acceptable sheet width	90mm~1,040mm (3.54"~40.9")	90mm~1,580mm (3.54"~62.0")	90~1,880mm (3.54"~74")
Acceptable roll sheet	Outer less than ϕ 200mm, Roll weight less than 18kg		Outer less than ϕ 200mm Roll weight less than 22kg
Effective cutting area*1	760mm x 51m (29.9" x 167')	1,300mm x 51m (51.2" x 167')	1,600mm x 51m (62.9" x 167')
Maximum auto cutting width*2	870mm (34.2")	1,425mm (56.1")	1,720mm (67.7")
Maximum cutting speed	100cm/s (39.3"/s)		
Maximum moving speed	140cm/s (55"/s)		
Adjustable speed range*3	1-10cm/s : 1cm step adjustment (0.39"~3.94"/s : 0.39" step adjustment)		
	10-50cm/s : 5cm step adjustment (3.94"~19.68"/s : 2" step adjustment)		
	50-100cm/s : 10cm step adjustment (19.68"~39.37" : 3.94" step adjustment)		
Mechanical resolution	5 μ m (0.0002")		
Command resolution	25 μ m or 10 μ m (0.001" or 0.0004")-MGL-lic		
Repeatability	\pm 0.2mm (Excluding shrinkage /expansion caused by the film temperature)		
Pen pressure	400g		
Range of down pressure	Cutter	10~20g(2g step), 20~100g(5g step), 100~400g(10g step)	
	Pouncing	10~20g(2g step), 20~100g(5g step), 100~400g(10g step)	
	Pen	10~20g(2g step), 20~100g(5g step), 100~150g(10g step)	
Acceptable sheet*4	Vinyl up to 0.15mm(0.006")thickness, Fluorescent type vinyl Reflective sheet		
Acceptable sheet for pouncing*5	Paper thickness: 0.06~0.13mm (0.0024"~0.005")		
Applicable tools*6	Cutter, Water based ball-point pen Oil based ball-point pen, Pouncing tool		
Type of command	MGL-lic		
Interface	RS-232C, USB		
Receiver buffer size	30MB Standard (20MB when in sorting)		
Operational Environment	Temperature	5~35°C (41~95 °F)	
	Humidity	35~75%(Rh) Non-condensation	
Power requirement	AC100V~240V		
Power consumption	130VA or less		
Dimensions (WxDxH)	1,285mm (50.5")x700mm (27.5")x1,217mm (47.9")	1,825mm (71.8")x700mm (27.5")x1,217mm (47.9")	2,125mm (83.6")x700mm (27.5")x1,217mm (47.9")
Weight (with stands)	50kg (110 lbs.)	60kg (132 lbs.)	69kg (152 lbs.)

- *1: Maximum sheet feeding length differs depending on the software.
- *2: Sheet width to cut off from the roll.
- *3: Restricted sheet width.
- *4: Provided that the blade specific to fluorescent type vinyl (SPB-0007) and the blade specific to reflective sheet (SPB-0006) are used.
- *5: Pouncing tool intended specifically for pouncing shall be used.
- *6: The goods on the market are ϕ 8- ϕ 9 Pen. No garranty with accuracy, and image quality.

Optional Tools and Accessories

	CG-75FX	CG-130FX	CG-160FX
Cutter holder		SPA-0090	
Blade for sheet cutter		SPA-0119	
Pouncing set	OPT-C0095 (Holder x 1, Needle x 2)		
Pen-line rubber	SPC-0358	SPC-0353	SPC-0381
Pen-line sponge	SPC-0359	SPC-0354	SPC-0382
Roll set	OPT-C0185	OPT-C0183	OPT-C0187
Sheet basket	OPT-C0184	OPT-C0182	OPT-C0186

Variety of Blades

	CG-75FX	CG-130FX	CG-160FX
Standard Blade for Vinyl		SPB-0030	
For Reflective sheet		SPB-0006	
For Fluorescent sheet		SPB-0007	
For Vinyl sheet and paper		SPB-0001	
For Small character		SPB-0003	

● All trademarks or registered trademarks are the property of the respective owners. ● Specifications are subject to change without notice.

All our products are manufactured under our quality assurance system certified by ISO9001



DISTRIBUTOR:

DEALER:

